



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

First Named

Inventor : Douglas J. Kerkvliet

Appln. No. : 09/873,481

Filed : June 4, 2001

Title : HYDRAULICALLY OPERATED
OVERHEAD DOOR

Docket No. : C535.12-0002

Group Art Unit: 3634

Examiner: J. Redman

EXPRESS MAIL COVER SHEET

SENT VIA EXPRESS MAIL

Assistant Commissioner for Patents
Washington, D.C. 20231

Express Mail No.: EL705882108US

Sir:

The following papers are being transmitted via **EXPRESS MAIL** to the U.S. Patent and Trademark Office on the date shown below:

1. Response

Respectfully submitted,

KINNEY & LANGE, P.A.

Date: November 18, 2002

By


Peter Sawicki
Peter Sawicki, Reg. No. 30,214
THE KINNEY & LANGE BUILDING
312 South Third Street
Minneapolis, MN 55415-1002
Telephone: (612) 339-1863
Fax: (612) 339-6580

ZPS:cnj

RECEIVED
NOV 21 2002
GROUP 3600

#908
11/22/02
3634

11-19-02



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

First Named		
Inventor	: Douglas J. Kerkvliet	
Appln. No.	: 09/873,481	
Filed	: June 4, 2001	Group Art Unit: 3634
Title	: HYDRAULICALLY OPERATED OVERHEAD DOOR	Examiner: J. Redman
Docket No.	: C535.12-0002	

RESPONSE

Box Non-Fee Amendment
Assistant Commissioner for Patents
Washington, D.C. 20231

SENT VIA EXPRESS MAIL

Express Mail No.: EL 705882108 US

Sir:

This is in response to the Office Action mailed on September 9, 2002.

IN THE CLAIMS

The claims as presently pending are provided for the Examiner's convenience.

36. An overhead door assembly for a building having an opening to be closed by a door, the door assembly having a vertical closed position and a horizontal open position and the door assembly having dimensions that are substantially equal to the building opening, comprising:

a frame, comprising a horizontal support member and first and second vertical members fixedly mounted to either end of the horizontal member, the vertical members fixedly mounted to a ground portion;

a one-piece door member having a thickness including top and bottom horizontal ends and first and second vertical sides, the top horizontal end of the door member pivotally mountable to the horizontal member of the frame and the door member movable from the closed position to the open position about the pivot point;

RECEIVED
NOV 21 2002
GROUP 3600